

Combination signaling device EN 54-23 cat. W+C, red flash



Part-No.: CWSS-RR-S5

Approval: VdS

Combined acoustic and optical alarm signaling device is EN 54-3 & EN 54-23 compliant, in red housing, and offers a selection of 32 signal tones including the DIN tone and other country-specific tones. All tones comply with EN 54-3. Tone configuration takes place via a 6-pin DIP switch. Up to two different signal tones may be activated. The optical signaling device with red signal lamp is suitable in accordance with EN 54-23 for square signal ranges W-2.4-6.8 and cylindrical signal ranges C-3-8.9 / C-6-8.2. Signaling device with flat base, suitable for wall and ceiling mounting.


To help define your conventional Visual Alarm Devices (VADs) requirements in line with the EN54-23 standard, we have developed an easy to use online guide. Simply enter the room dimensions and ambient light conditions and the guide will help your device selection: https://www.kac.co.uk/device_estimator/

Features:

- EN 54-3 and 54-23 compliant
- Synchronous sound and flash trigger
- Volume adjustable to 2 levels at the device
- C & W category
- Signal range up to 6.0 m room width for wall mounting
- Signal range up to 8.9 m room diameter for ceiling mounting

Common technical data

Operating voltage	12 ... 29 V DC
Current consumption @ 12 V DC	approx. 63.9 mA (@ DIN tone)
Current consumption @ 24 V DC	approx. 69.9 mA (@ DIN tone)
Sound level @ 12 V DC	97 dB(A) (@ DIN tone)
Sound level @ 24 V DC	102.7 dB(A) (@ DIN tone)
Frequency of flash	0.5 Hz
Flash color	red
Luminous intensity	max. 56 cd effective
Connection terminal	0.5 ... 2.5 mm ²
Ambient temperature	-25 °C ... 70 °C
Air humidity	< 95 % (non-condensing)
Type of protection	IP 21C, IP 65 with CWW and accessories
Mounting height wall	2.4 m
Room width	6,8 m
Color	red, similar to RAL 3020
Weight	approx. 248 g
Dimensions	Ø: 100 mm H: 98 mm
Declaration of Performance	0832-CPR-F0262

 Not suitable for use outdoors or in damp areas. Please use therefore the optional bases and accessories (Part No. CWR, PS188, PS189). Use of the deep IP socket reduces the dB output by an average of 4 dB. When using the EOL-O 808624 termination element for standard-compliant monitoring of the alarm devices, the optional deep base CWR or CWW offers a larger connection space. Replacement for Part No. 766430.

Accessories:

CWR	Base deep IP 65, red
PS188	Base deep, O-Ring
PS189	Base deep, seal